

1	2	3	4	5	6	7	8
H							
G							
F							
E							
D							
C							
B							
A							

SPECIFICATION FOR APPROVAL



MARKETING GROUP	R&D GROUP	QA GROUP
ISSUED BY	CHECKED BY	QA INSPECTION
chen	Weide Li	Ting Liu

CUSTOMER

CUSTOMER APPROVAL:

☐ APPROVAL ☐ CONCESSIONARY ☐ REJECTED

ISSUED BY : _____

CHECKED BY: _____

APPROVED BY: _____

CUSTOMER: _____

CUSTOMER PART NO: _____

SAMPLE Q'TY: _____

COMMENTS : _____

TITLE						 多亞電子有限公司 Duoya Electronics Co.,Ltd		
PART NO. DY58-HD13058-001				GENERAL TOLERANCE			UNIT: MM(INCH)	SIZE: A4
DRAW	Chen	DATE	2026-09-08	.X±0.35	.X±1°	SCALE: 1:1	SHEET: 1/5	REV: A
CHECK	Weide Li	DATE	2026-09-08	.XX±0.25	.XX±0.5°			
APPROVE	De	DATE	2026-09-08	.XXX				

THIS DRAWING IS A CONTROLLED DOCUMENT FOR DUOYA CONNECTOR CORPORATION


EMAIL: INFO@DELEC.COM.CN WEB SITE: HTTP://WWW.DELEC.COM.CN

BY DUOYA CONNECTOR CORPORATION

© COPYRIGHT 2010

PRODUCT DRAWING

MECHANICAL DIMENSION



SPECIFICATION AND PERFORMANCE

1 Scope

This specification covers the requirements for product performance, tests and quality assurance provisions for side entry PCB jack

2 Applicable document

The following documents form a part of this specification to the extent specified herein. In the event of conflict between the requirements of this specification and the product drawing shall take precedence

3 Materials

Plastic Housing: Glass filled polyester PBT UL94V-0

(color : pantone Black)

Contact: phosphor bronze Ø=0.46mm round Pin

Plating: F u" Gold plating over nickel

PCB retention fre-solder: 1LB min.

4. Mechanical characteristics:

Durability: 750(modular jack) insertion/plug dimension cycles

Mates with modular plug conforming to FCC part 68 subpart F

5. Electrical

Current rating: 1.5AMP

Voltage rating: 125VAC max.

Contact resistance: 30 milliohms max.

Insulation resistance: 500 megohms min.@500 VDC.

Dielectric strength: 1000 VAC RMS 60Hz, 1min.

6. Environmental:


Operating temperature: -40°C~+85°C

Storage temperature: -40°C~+85°C

7. Applicable printed circuit board

The product is designed to meet the electrical, mechanical and environmental performance requirements specified in product drawing

TITLE						 多亞電子有限公司 Duoya Electronics Co.,Ltd			
1X3 RJ45 8P8C SIDE ENTRY JACK WITHOUT LED									
PART NO. DY58-HD13058-001				GENERAL TOLERANCE			UNIT:MM(INCH)	SIZE: A4	
DRAW	Chen	DATE	2026-09-08	.X±0.35	.X±1°		SCALE: 1:1	SHEET: 3/5	REV: A
CHECK	Weide Li	DATE	2026-09-08	.XX±0.25	.XX±0.5°				
APPROVE	De	DATE	2026-09-08	.XXX					



TITLE						 多亞電子有限公司 Duoya Electronics Co.,Ltd			
1X3 RJ45 8P8C SIDE ENTRY JACK WITHOUT LED									
PART NO. DY58-HD13058-001				GENERAL TOLERANCE			UNIT:MM(INCH)	SIZE: A4	
DRAW	Chen	DATE	2026-09-08	.X±0.35	.X±1°		SCALE: 1:1	SHEET: 4/5	REV: A
CHECK	Weide Li	DATE	2026-09-08	.XX±0.25	.XX±0.5°				
APPROVE	De	DATE	2026-09-08	.XXX					

H

PACKAGE INFORMATION AND LABEL

G

F


E

D

C

B

A



PACKING QUANTITY : 50 PCS FINISHED GOODS PER TRAY
12 TRAYS (600 PCS FINISHED GOODS) PER CARTON BOX

TITLE 1X3 RJ45 8P8C SIDE ENTRY JACK WITHOUT LED						多亞電子有限公司 Duoya Electronics Co.,Ltd		
PART NO. DY58-HD13058-001				GENERAL TOLERANCE			UNIT: MM(INCH)	SIZE: A4
DRAW	Chen	DATE	2026-09-08	.X±0.35	.X±1°	SCALE: 1:1	SHEET: 5/5	REV: A
CHECK	Weide Li	DATE	2026-09-08	.XX±0.25	.XX±0.5°			
APPROVE	De	DATE	2026-09-08	.XXX				