

1	2	3	4	5	6	7	8	
H								
G								
F								
E								
D								
C								
B								
A								

SPECIFICATION FOR APPROVAL



MARKETING GROUP	R&D GROUP	QA GROUP
ISSUED BY	CHECKED BY	QA INSPECTION
CHEN	Weide Li	Liu Ting

CUSTOMER

CUSTOMER APPROVAL:

☐ APPROVAL ☐ CONCESSIONARY ☐ REJECTED

ISSUED BY : _____

CHECKED BY: _____


APPROVED BY: _____

COMMENTS : _____

CUSTOMER: _____

CUSTOMER PART NO: _____

SAMPLE Q'TY: _____

TITLE						 多亞電子有限公司 Duoya Electronics Co.,Ltd		
PART NO.				GENERAL TOLERANCE			UNIT:MM(INCH)	SIZE: A4
DRAW	chen	DATE	2026-07-31	.X±0.35	.X±1°	SCALE: 1:1	SHEET: 1/4	REV:A
CHECK	Li	DATE	2026-07-31	.XX±0.25	.XX±0.5°			
APPROVE	De	DATE	2026-07-31	.XXX				

THIS DRAWING IS A CONTROLLED DOCUMENT FOR DUOYA CONNECTOR CORPORATION


EMAIL: INFO@DELEC.COM.CN WEB SITE: HTTP://WWW.DELEC.COM.CN

BY DUOYA CONNECTOR CORPORATION

PRODUCT DRAWING

© COPYRIGHT 2010

	1	2	3	4	5	6	7	8
H	ISSUE RECORD							
G	REV	DESCRIPTION OF CHANGE			REVIEWED BY	APPROVED BY	ISSUE DATE	
	A	FIRST ISSUE			chen	De	2026-07-31	
F								
E								
D								
C								
B								
A								

TITLE						 多亞電子有限公司 Duoya Electronics Co.,Ltd			
PART NO.				GENERAL TOLERANCE			UNIT:MM(INCH)	SIZE: A4	
DRAW	chen	DATE	2026-07-31	.X±0.35	.X±1°		SCALE: 1:1	SHEET: 2/4	REV:A
CHECK	Li	DATE	2026-07-31	.XX±0.25	.XX±0.5°				
APPROVE	De	DATE	2026-07-31	.XXX					

THIS DRAWING IS A CONTROLLED DOCUMENT FOR DUOYA CONNECTOR CORPORATION


EMAIL: INFO@DELEC.COM.CN WEB SITE: HTTP://WWW.DELEC.COM.CN

PRODUCT DRAWING

BY DUOYA CONNECTOR CORPORATION

© COPYRIGHT 2010

MECHANICAL DIMENSION



RECOMMENDED PCB LAYOUT
(COMPONENT SIDE VIEW)

SPECIFICATION AND PERFORMANCE

1 Scope

This specification covers the requirements for product performance, tests and quality assurance provisions for side entry PCB jack

2 Applicable document

The following documents form a part of this specification to the extent specified herein. In the event of conflict between the requirements of this specification and the product drawing shall take precedence

3 Materials

Housing: Glass filled polyester(PBT) UL94V-0, pantone Black
Contact: phosphor bronze 0.35mm flat Pin
Plating: 6 u"Gold plating over nickel
Shielded: 0.20 thickness brass with nickel plated.
PCB retention fre-solder: 1LB min.

4 Mechanical characteristics:

Durability: 750(modular jack) insertion/plug dimension cycles
Mates with modular plug conforming to FCC part 68 subpart F.

5 Electrical

Current rating: 1.5AMP
Voltage rating: 125VAC max.
Contact resistance: 30 milliohms max.
Insulation resistance: 500 megohms min.@500 VDC.
Dielectric strength: 1000 VAC RMS 60Hz, 1min.


6 Environmental:

Operating temperature: -40°C~+85°C
Storage temperature: -40°C~+85°C

7 Applicable printed circuit board

The product is designed to meet the electrical, mechanical and environmental performance requirements specified in product drawing

TITLE 1X1 RJ45 10P8C SIDE ENTRY JACK WITHOUT LED						 多亞電子有限公司 Duoya Electronics Co.,Ltd		
PART NO. DY56-SD11506-00G				GENERAL TOLERANCE			UNIT:MM(INCH)	SIZE: A4
DRAW	chen	DATE	2026-07-31	.X±0.35	.X±1°	SCALE: 1:1	SHEET: 3/4	REV:A
CHECK	Li	DATE	2026-07-31	.XX±0.25	.XX±0.5°			
APPROVE	De	DATE	2026-07-31	.XXX				



PACKING QUANTITY : 80 PCS FINISHED GOODS PER TRAY
14 TRAYS (1120 PCS FINISHED GOODS) PER CARTON BOX

TITLE 1X1 RJ45 10P8C SIDE ENTRY JACK WITHOUT LED						多亞電子有限公司 Duoya Electronics Co.,Ltd		
PART NO. DY56-SD11506-00G				GENERAL TOLERANCE			UNIT:MM(INCH)	SIZE: A4
DRAW	chen	DATE	2026-07-31	.X±0.35	.X±1°	SCALE: 1:1	SHEET: 4/4	REV:A
CHECK	Li	DATE	2026-07-31	.XX±0.25	.XX±0.5°			
APPROVE	De	DATE	2026-07-31	.XXX				