

1	2	3	4	5	6	7	8	
H								
G								
F								
E								
D								
C								
B								
A								

SPECIFICATION FOR APPROVAL



MARKETING GROUP	R&D GROUP	QA GROUP
ISSUED BY	CHECKED BY	QA INSPECTION
chen	Weide Li	DE

CUSTOMER

CUSTOMER APPROVAL:

☐ APPROVAL ☐ CONCESSIONARY ☐ REJECTED

ISSUED BY : _____

CHECKED BY: _____


APPROVED BY: _____

COMMENTS : _____

CUSTOMER: _____

CUSTOMER PART NO: _____


SAMPLE Q'TY: _____

TITLE 2X2 RJ45 8P8C SIDE ENTRY JACK WITHOUT LED						 多亞電子有限公司 Duoya Electronics Co.,Ltd		
PART NO. DY60-3A1BT05-00G				GENERAL TOLERANCE			UNIT: MM(INCH)	SIZE: A4
DRAW	chen	DATE	2026-07-24	.X±0.35	.X±1°	SCALE: 1:1	SHEET: 1/5	REV: A
CHECK	weide li	DATE	2026-07-24	.XX±0.25	.XX±0.5°			
APPROVE	De	DATE	2026-07-24	.XXX				

THIS DRAWING IS A CONTROLLED DOCUMENT FOR DUOYA CONNECTOR CORPORATION EMAIL: INFO@DELEC.COM.CN WEB SITE: HTTP://WWW.DELEC.COM.CN

BY DUOYA CONNECTOR CORPORATION
© COPYRIGHT 2010
PRODUCT DRAWING

	1	2	3	4	5	6	7	8
H	ISSUE RECORD							
G	REV	DESCRIPTION OF CHANGE			REVIEWED BY	APPROVED BY	ISSUE DATE	
	A	FIRST ISSUE			chen	De	2026-07-24	
F								
E								
D								
C								
B								
A								

TITLE						 多亞電子有限公司 Duoya Electronics Co.,Ltd		
PART NO.				GENERAL TOLERANCE			UNIT: MM(INCH)	SIZE: A4
DRAW	chen	DATE	2026-07-24	.X±0.35	.X±1°	SCALE: 1:1	SHEET: 2/5	REV: A
CHECK	weide li	DATE	2026-07-24	.XX±0.25	.XX±0.5°			
APPROVE	De	DATE	2026-07-24	.XXX				

THIS DRAWING IS A CONTROLLED DOCUMENT FOR DUOYA CONNECTOR CORPORATION






EMAIL: INFO@DELEC.COM.CN WEB SITE: HTTP://WWW.DELEC.COM.CN

PRODUCT DRAWING

BY DUOYA CONNECTOR CORPORATION

© COPYRIGHT 2010

MECHANICAL DIMENSION



SPECIFICATION AND PERFORMANCE

1 Scope

This specification covers the requirements for product performance, tests and quality assurance provisions for side entry PCB jack

2 Applicable document

The following documents form a part of this specification to the extent specified herein. In the event of conflict between the requirements of this specification and the product drawing shall take precedence

3 Materials

Housing: Glass filled polyester UL94V-0, pantone Black(PA46)

Contact: Phosphor Bronze T=0.35 mm Flat Pin

Shielded: Stainless Steel (T=0.20mm); Pins: Pre-tinning of stainless steel

Plating: 6U"Gold plating over nickel

4. Mechanical characteristics:

Durability: 750(modular jack) insertion/plug dimension cycles

Mates with modular plug conforming to FCC part 68 subpart F

5. Electrical

Current rating: 1.5AMP

Voltage rating: 125VAC max.

Contact resistance: 30 milliohms max.

Insulation resistance: 500 megohms min.@500 VDC.

Dielectric strength: 1000 VAC RMS 60Hz, 1min.

6. Environmental:


Operating temperature: -40℃~+85℃

Storage temperature: -40℃~+85℃


7. Applicable printed circuit board

The product is designed to meet the electrical, mechanical and environmental performance requirements specified in product drawing


TITLE 2X2 RJ45 8P8C SIDE ENTRY JACK WITHOUT LED						 多亞電子有限公司 Duoya Electronics Co.,Ltd		
PART NO. DY60-3A1BT05-00G				GENERAL TOLERANCE			UNIT:MM(INCH)	SIZE: A4
DRAW	chen	DATE	2026-07-24	.X±0.35	.X±1°	SCALE: 1:1	SHEET: 3/5	REV: A
CHECK	weide li	DATE	2026-07-24	.XX±0.25	.XX±0.5°			
APPROVE	De	DATE	2026-07-24	.XXX				




RECOMMENDED PCB LAYOUT
(COMPONENT SIDE VIEW)

TITLE 2X2 RJ45 8P8C SIDE ENTRY JACK WITHOUT LED						 多亞電子有限公司 Duoya Electronics Co.,Ltd		
PART NO. DY60-3A1BT05-00G				GENERAL TOLERANCE			UNIT: MM(INCH)	SIZE: A4
DRAW	chen	DATE	2026-07-24	.X±0.35	.X±1°	SCALE: 1:1	SHEET: 4/5	REV: A
CHECK	weide li	DATE	2026-07-24	.XX±0.25	.XX±0.5°			
APPROVE	De	DATE	2026-07-24	.XXX				

PACKAGE INFORMATION AND LABLE



PACKING QUANTITY : 40 PCS FINISHED GOODS PER TRAY
10 TRAYS (400 PCS FINISHED GOODS) PER CARTON BOX

TITLE 2X2 RJ45 8P8C SIDE ENTRY JACK WITHOUT LED						 多亞電子有限公司 Duoya Electronics Co.,Ltd		
PART NO. DY60-3A1BT05-00G				GENERAL TOLERANCE			UNIT: MM(INCH)	SIZE: A4
DRAW	chen	DATE	2026-07-24	.X±0.35	.X±1°	SCALE: 1:1	SHEET: 5/5	REV: A
CHECK	weide li	DATE	2026-07-24	.XX±0.25	.XX±0.5°			
APPROVE	De	DATE	2026-07-24	.XXX				